

Att'y Ref. No.: 003-089

U.S. App. No.: 10/676,087

1. (Currently Amended) A seal assembly comprising:
a layered structure including
a first layer of a base material;
a second layer of thermal insulating material on top of the first layer, said thermal insulating material having a thermal conductivity substantially lower than the thermal conductivity of the base material;
a third layer of a base material on top of the layer of thermal insulation;
a spring side support; and
wherein the layered structure is connected on two sides to the spring side support.
2. (Original) The seal assembly according to claim 1, wherein the layer of thermal insulating material comprises a woven insulating material.
3. (Original) The seal assembly according to claim 1, wherein the third layer of the seal assembly comprises oxidation resistant material.
4. (Original) The seal assembly according to claim 1, further comprising:
a connector plate having an inner connector band and an outer connector band; and
wherein the layered structure is arranged within the connector plate with the first layer comprising the inner connector band and the third layer comprising the outer connector band.
5. (Previously Presented) The seal assembly according to claim 4, wherein the first layer is welded to the third layer.
6. (Previously Presented) The seal assembly according to claim 4, wherein the connector plate is connected on two sides to the spring side support.

[Page 2 of 11]

Att'y Ref. No.: 003-089

U.S. App. No.: 10/676,087

7. (Withdrawn) The seal assembly according to claim 6, wherein the spring side support comprises an E-seal.
8. (Previously Presented) The seal assembly according to claim 6, wherein the spring side support is welded to the connector plate.
9. (Withdrawn) The seal assembly according to claim 4, further comprising:
an E-seal having two sides; and
wherein the connector plate is bent around and fixed to the two sides of the E-seal.
10. (Previously Presented) The seal assembly according to claim 1, further comprising:
cooling holes arranged within the spring side support.
11. (Withdrawn) The seal assembly according to claim 1, further comprising:
two E-seals; and
wherein the layer of thermal insulating material is arranged between the two E-seals as said first and third layers.
12. (Previously Presented) The seal assembly according to claim 1, further comprising:
combustor liner segments; and
a combustor liner seal between the combustor liner segments, said combustor liner seal comprising said layered structure.
13. (Withdrawn) The seal assembly according to claim 9, further comprising:
cooling holes arranged within the E-seal.

[Page 3 of 11]

Att'y Ref. No.: 003-089

U.S. App. No.: 10/676,087

14. (Currently Amended) A seal assembly comprising:
a layered structure including
a first layer of a base material,
a second layer of thermal insulating material on top of the first layer, said thermal insulating material having a thermal conductivity substantially lower than the thermal conductivity of the base material; and
a third layer of a base material on top of the layer of thermal insulation;
combustor liner segments; and
a combustor liner seal between the combustor liner segments, said combustor liner seal comprising said layered structure.
15. (Previously Presented) The seal assembly according to claim 14, wherein the layer of thermal insulating material comprises a woven insulating material.
16. (Previously Presented) The seal assembly according to claim 14, wherein the third layer of the seal assembly comprises oxidation resistant material.
17. (Previously Presented) The seal assembly according to claim 14, further comprising:
a connector plate having an inner connector band and an outer connector band; and
wherein the layered structure is arranged within the connector plate with the first layer comprising the inner connector band and the third layer comprising the outer connector band.
18. (Previously Presented) The seal assembly according to claim 17, wherein the first layer is welded to the third layer.
19. (Previously Presented) The seal assembly according to claim 14, further comprising:

[Page 4 of 11]

Att'y Ref. No.: 003-089

U.S. App. No.: 10/676,087

a spring side support connected to the layered structure.

20. (Previously Presented) The seal assembly according to claim 19, further comprising:

cooling holes arranged within the spring side support.

21. (New) A seal assembly comprising:

a layered structure including

a first layer of a base material;

a second layer of thermal insulating material on top of the first layer, said thermal insulating material having a thermal conductivity substantially lower than the thermal conductivity of said base material;

a third layer of a base material on top of the layer of thermal insulation;

a spring side support; and

wherein the layered structure is connected on two sides to the spring side support, such that said first layer and said third layer are connected with each other at said two sides and the second layer is held between said first and third layers.

22. (New) The seal assembly according to claim 21, wherein the layer of thermal insulating material comprises a woven insulating material.

23. (New) The seal assembly according to claim 21, wherein the third layer of the seal assembly comprises oxidation resistant material.

24. (New) The seal assembly according to claim 21, further comprising:
a connector plate having an inner connector band and an outer connector band; and
wherein the layered structure is arranged within the connector plate with the first layer comprising the inner connector band and the third layer comprising the outer connector band.

[Page 5 of 11]

Att'y Ref. No.: 003-089

U.S. App. No.: 10/676,087

25. (New) The seal assembly according to claim 24, wherein the first layer is welded to the third layer.
26. (New) The seal assembly according to claim 24, wherein the connector plate is connected on two sides to the spring side support.
27. (New) The seal assembly according to claim 26, wherein the spring side support comprises an E-seal.
28. (New) The seal assembly according to claim 26, wherein the spring side support is welded to the connector plate.
29. (New) The seal assembly according to claim 24, further comprising:
an E-seal having two sides; and
wherein the connector plate is bent around and fixed to the two sides of the E-seal.
30. (New) The seal assembly according to claim 29, further comprising:
cooling holes arranged within the E-seal.
31. (New) The seal assembly according to claim 21, further comprising:
cooling holes arranged within the spring side support.
32. (New) The seal assembly according to claim 21, further comprising:
two E-seals; and
wherein the layer of thermal insulating material is arranged between the two E-seals as said first and third layers.

[Page 6 of 11]

Att'y Ref. No.: 003-089

U.S. App. No.: 10/676,087

33. (New) The seal assembly according to claim 21, further comprising:
combustor liner segments; and
a combustor liner seal between the combustor liner segments, said combustor liner seal
comprising said layered structure.

[Page 7 of 11]